

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 0 984 400 A2**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
08.03.2000 Bulletin 2000/10

(51) Int. Cl.7: **G07C 5/08, G09F 3/03**

(21) Application number: **99202820.9**

(22) Date of filing: **31.08.1999**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• Haimovich, Yosef
Rishon le Zion 75258 (IL)
• Armoni, Yehuda
Reut 71908 (IL)
• Auerbach, Michael
Maccabim 71908 (IL)

(30) Priority: **31.08.1998 IL 12600898**

(71) Applicant: **Hi-G-Tek Ltd**
Or Yehuda 60375 (IL)


(74) Representative:
Ungria Lopez, Javier et al
Avda. Ramon y Cajal, 78
28043 Madrid (ES)

(54) **Electronic monitoring apparatus**

(57) Electronic monitoring apparatus (10) including an object (14) to be protected, an electronic seal body (12) integrally formed with the object (14) to be protected, and an electronic seal wire (16) attachable to the seal body (12), characterized by the seal wire (16) having an electrical signature which is not readable without

disengagement of the seal wire (16) from the seal body (12), and electronic seal circuitry (18) in electrical communication with the seal wire (16) which senses a change in the electrical signature.

FIG. 1



EP 0 984 400 A2

Description

FIELD OF THE INVENTION

[0001] The present invention relates electronic seals generally, and particularly to RF-interrogated identification tags and electronic seals.

BACKGROUND OF THE INVENTION

[0002] Electronic tags are known that can be monitored, sensed, or interrogated for purposes of preventing theft of or tampering with the object. For example, applicant/assignee's U.S. Patent Application No. 08/815,389, the disclosure of which is incorporated herein by reference, describes a battery-operated electronic tag that, when tampered with, communicates via a transceiver to a detection system for providing an alarm signal or other indication. One embodiment disclosed in 08/815,389 is directed to a tag with a seal wire which comprises a multiplicity of resistive wires, preferably constructed of a high resistivity material such as nickel chrome. Each wire is insulated from each other and from the external world. A random number of wires are electrically connected to electrical pins of the tag. The random connection results in a statistically random electrical resistance of the seal wire, which resistance cannot be measured from the outside of the tag. This electronic tag has already enjoyed commercial success and is marketed under the trade name HI-G-SEAL.

[0003] US Patent 4,766,419 to Hayward describes a reusable seal for a vehicle or container which includes a housing, and a cable secured at one end to the housing and releasably attached to the housing at the other end by a locking mechanism. Operation of the locking mechanism causes an electronic circuit in the housing to generate a random number, which is displayed by an LED display when a button is pressed. Any change in the number displayed indicates that the cable has been released. The seal can be repeatedly re-used.

[0004] US Patent 5,447,344, also to Hayward, describes an electronic seal including a housing, a flexible element extending from the housing and having a free end which can be passed through a door catch device for releasably connecting the free end of the flexible element to the housing, an electronic circuit within the housing arranged to generate one of a number of unique codes on receipt of an electrical signal and to store the generated code, display device on the housing adapted to display the generated code, and a switch on the housing actuated on connection or disconnection of the flexible element to the housing to provide an electrical signal to actuate the electronic circuit. The flexible element is a cord having a series of regularly spaced enlargements, and the device for releasably connecting the free end of the cord to the housing comprises a passage in the housing into which a length of the cord can be inserted, a number of teeth in the housing being

adapted to fit between enlargements of the cord, so that when the length of cord is inserted into the housing each enlargement of the length of cord can fit between two adjacent teeth to hold the cord against withdrawal from the housing, and a slide movable in the housing between a first position in which the cord can be inserted and removed from the passage, and a second position in which the slide retains the enlargements in engagement with the teeth. The switch has an actuating member projecting between two of the teeth, so as to be engaged by one of the enlargements on the cord when it is engaged between the teeth, so that the switch is actuated when the length of cord is moved into or out of engagement with the teeth.

[0005] It is noted that in both patents of Hayward there is no sealing wire with a signature. Instead the electrical circuitry in the seal housing generates a random signature.

SUMMARY OF THE INVENTION

[0006] The present invention seeks to provide a novel electronic seal, based on the technology of the seal wire described in 08/815,389, wherein the electronic seal is integrated with the object to be protected. The body of the electronic seal is integrally formed with the object to be protected, or may be embedded, bonded, fastened or otherwise attached to the object to be protected. The seal wire has a signature which is not readable without disengaging the seal wire from the seal body, and any such disengaging is sensed by the electronic seal circuitry.

[0007] There is thus provided in accordance with a preferred embodiment of the present invention electronic monitoring apparatus including an object to be protected, an electronic seal body integrally formed with the object to be protected, an electronic seal wire attachable to the seal body, the seal wire having an electrical signature which is not readable without disengagement of the seal wire from the seal body, and electronic seal circuitry in electrical communication with the seal wire which senses a change in the electrical signature.

[0008] There is also provided in accordance with a preferred embodiment of the present invention electronic monitoring apparatus including an object to be protected, an electronic seal body including two halves, each half attached to the object to be protected, an electronic seal wire having two ends each of which is attachable to one of the halves of the seal body, the seal wire having an electrical signature which is not readable without disengagement of the seal wire from the seal body, and electronic seal circuitry in electrical communication with the seal wire which senses a change in the electrical signature.

[0009] In accordance with a preferred embodiment of the present invention the object includes a door and an enclosure, and wherein one of the halves is attached to

the door and the other half is attached to a portion of the enclosure, wherein the door is openable only under two conditions: a) tampering with the seal wire, b) disengagement of the seal wire from the seal body.

[0010] Further in accordance with a preferred embodiment of the present invention the halves are in electrical communication with each other.

[0011] Still further in accordance with a preferred embodiment of the present invention the halves are in electrical communication with each other via the seal wire.

[0012] There is also provided in accordance with a preferred embodiment of the present invention a method for protecting an object including integrally forming an electronic seal body with an object to be protected, providing an electronic seal wire separately from the seal body, attaching the electronic seal wire to the seal body, the seal wire having an electrical signature which is not readable without disengagement of the seal wire from the seal body, and sensing a change in the electrical signature.

[0013] In accordance with a preferred embodiment of the present invention the electronic seal body is formed with the object by a manufacturer of the object and the electronic seal wire is provided to a user of the object.

[0014] Further in accordance with a preferred embodiment of the present invention the method includes communicating with at least one of the electronic seal body and the electronic seal wire by means of encrypted communication.

[0015] Still further in accordance with a preferred embodiment of the present invention the encrypted communication includes a mutual zero-knowledge interaction authentication session.

BRIEF DESCRIPTION OF THE DRAWINGS

[0016] The present invention will be understood and appreciated more fully from the following detailed description, taken in conjunction with the drawings in which:

Fig. 1 is a simplified pictorial illustration of electronic monitoring apparatus constructed and operative in accordance with a preferred embodiment of the present invention; and

Figs. 2, 3 and 4 are simplified pictorial illustrations of electronic monitoring apparatus constructed and operative in accordance with three preferred embodiments of the present invention, wherein the electronic monitoring apparatus includes an electronic seal body with two halves.

DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT

[0017] Reference is now made to Fig. 1 which illustrates electronic monitoring apparatus 10 constructed

and operative in accordance with a preferred embodiment of the present invention.

[0018] Apparatus 10 preferably includes an electronic seal body 12 integrally formed with an object 14 to be protected. In the illustrated embodiment, the object 14 is a semi-trailer, and seal body 12 is integrally formed with the back door of the trailer. Alternatively, seal body 12 may be embedded, bonded, fastened or otherwise attached to object 14.

[0019] An electronic seal wire 16 is attachable to seal body 12. Seal wire 16 has an electrical signature which cannot be read or detected from outside the seal without disengagement of seal wire 16 from seal body 12, in accordance with the teachings of U.S. Patent Application No. 08/815,389. As disclosed in 08/815,389, electronic seal circuitry 18 is provided which is in electrical communication with seal wire 16 and senses a change in the electrical signature of seal wire 16. Thus if any attempt is made to tamper with apparatus 10, electronic seal circuitry 18 alerts of such an attempt.

[0020] It is appreciated that electronic seal circuitry 18 may be housed in apparatus 10 or may be remotely located from apparatus 10 and in communication therewith. Communication with apparatus 10, including communication of any changes in the electrical signature of seal wire 16 to an alarm system, may be accomplished by any kind of suitable communication. In order to enhance security, communication with apparatus 10 may be encrypted. For example, well known encryption algorithms, such as RC-5, DES or DVB, may be employed. To provide an even greater level of trust, mutual zero-knowledge interaction authentication sessions between a monitoring station (not shown) and apparatus 10 may be held, such as the so-called Fiat-Shamir authentication methods taught in US Patent 4,748,668 to Shamir and Fiat, the disclosure of which is incorporated herein by reference.

[0021] An advantage of the present invention over the prior art is that seal body 12 may be attached to object 14 by the manufacturer, and seal wire 16 may be provided separately to authorized personnel.

[0022] Reference is now made to Figs. 2-4 which illustrate electronic monitoring apparatus 20 constructed and operative in accordance with a preferred embodiment of the present invention. Electronic monitoring apparatus 20 is similar in construction to electronic monitoring apparatus 10 with like numerals designating like elements. Electronic monitoring apparatus 20 differs from electronic monitoring apparatus 10 in that electronic monitoring apparatus 20 includes two halves 22 and 24, each half attached to an object 26 to be protected. In the illustrated embodiments, object 26 (in Fig. 2, a safe, in Fig. 3, a prison cell, in Fig. 4, a stable) includes a door 28 and an enclosure 30. Half 22 is attached to door 28 and the other half 24 is attached to a portion of enclosure 30. It is seen that door 28 is openable only by tampering with seal wire 16, or by disengaging seal wire 16 from seal body 12.

[0023] Half 22 is preferably in electrical communication with half 24 such as by means of seal wire 16 itself or alternatively an auxiliary wire.

[0024] It will be appreciated by persons skilled in the art that the present invention is not limited by what has been particularly shown and described hereinabove. Rather the scope of the present invention includes both combinations and subcombinations of the features described hereinabove as well as modifications and variations thereof which would occur to a person of skill in the art upon reading the foregoing description and which are not in the prior art.

Claims

1. Electronic monitoring apparatus (10, 20) comprising:

an object (14) to be protected; and
an electronic seal body (12) integrally formed with said object (14) to be protected; characterized by an electronic seal wire (16) attachable to said seal body (12), said seal wire (16) having an electrical signature which is not readable without disengagement of the seal wire (16) from the seal body (12); and electronic seal circuitry (18) in electrical communication with said seal wire (16) which senses a change in said electrical signature.

2. Electronic monitoring apparatus (20) comprising:

an object (14) to be protected;
an electronic seal body (12) comprising two halves (22, 24), each half (22, 24) attached to said object (14) to be protected;
an electronic seal wire (16) having two ends each of which is attachable to one of said halves (22, 24) of said seal body (12), said seal wire (16) having an electrical signature which is not readable without disengagement of the seal wire (16) from the seal body (12); and electronic seal circuitry (18) in electrical communication with said seal wire (16) which senses a change in said electrical signature.

3. Electronic monitoring apparatus (20) according to claim 2 wherein said object (14) comprises a door (28) and an enclosure (30), wherein one of said halves (22, 24) is attached to said door (28) and the other half (22, 24) is attached to a portion of said enclosure (30), wherein said door (28) is openable only under two conditions: a) tampering with said seal wire (16), b) disengagement of said seal wire (16) from said seal body (12).

4. Electronic monitoring apparatus (20) according to claim 2 wherein said halves (22, 24) are in electrical

communication with each other.

5. Electronic monitoring apparatus (20) according to claim 4 wherein said halves (22, 24) are in electrical communication with each other via said seal wire (16).
6. A method for protecting an object (14) comprising:
 - integrally forming an electronic seal body (12) with an object (14) to be protected;
 - providing an electronic seal wire (16) separately from said seal body (12);
 - attaching said electronic seal wire (16) to said seal body (12), said seal wire (16) having an electrical signature which is not readable without disengagement of the seal wire (16) from the seal body (12); and
 - sensing a change in said electrical signature.
7. The method according to claim 6 wherein said electronic seal body (12) is formed with the object (14) by a manufacturer of the object (14) and said electronic seal wire (16) is provided to a user of the object (14).
8. The method according to claim 6 and further comprising communicating with at least one of said electronic seal body (12) and said electronic seal wire (16) by means of encrypted communication.
9. The method according to claim 7 wherein said encrypted communication comprises a mutual zero-knowledge interaction authentication session.

FIG. 1




FIG. 2




FIG. 3





FIG. 4



THIS PAGE BLANK (USPTO)

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 984 400 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
12.09.2001 Bulletin 2001/37

(51) Int Cl.7: **G09F 3/03, G07C 5/08**

(43) Date of publication A2:
08.03.2000 Bulletin 2000/10

(21) Application number: **99202820.9**

(22) Date of filing: **31.08.1999**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• **Haimovich, Yosef**
Rishon le Zion 75258 (IL)
• **Armoni, Yehuda**
Reut 71908 (IL)
• **Auerbach, Michael**
Maccabim 71908 (IL)

(30) Priority: **31.08.1998 IL 12600898**

(71) Applicant: **Hi-G-Tek Ltd**
Or Yehuda 60375 (IL)


(74) Representative: **Ungria Lopez, Javier et al**
Avda. Ramon y Cajal, 78
28043 Madrid (ES)

(54) Electronic monitoring apparatus

(57) Electronic monitoring apparatus (10) including an object (14) to be protected, an electronic seal body (12) integrally formed with the object (14) to be protected, and an electronic seal wire (16) attachable to the seal body (12), characterized by the seal wire (16) hav-

ing an electrical signature which is not readable without disengagement of the seal wire (16) from the seal body (12), and electronic seal circuitry (18) in electrical communication with the seal wire (16) which senses a change in the electrical signature.

FIG. 1



EP 0 984 400 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 99 20 2820

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 5 097 253 A (ESCHBACH EUGENE A ET AL) 17 March 1992 (1992-03-17)	1,6	G09F3/03 G07C5/08
Y	* abstract *	2-5	
A	* column 1, line 45 - column 3, line 46 * * column 6, line 18 - line 39 *	7-9	
Y	US 4 523 186 A (FIARMAN SIDNEY) 11 June 1985 (1985-06-11)	2-5	
A	* abstract * * column 2, line 26 - column 3, line 27 *	1,7-9	
A	US 5 443 190 A (CUCHERAN JOHN S ET AL) 22 August 1995 (1995-08-22) * abstract * * column 2, line 41 - column 5, line 6 *	1,6,8,9	
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			G07C G09F
Place of search THE HAGUE		Date of completion of the search 24 July 2001	Examiner Teutloff, H
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EP0 FORM 1503 03 02 (P04001)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 20 2820

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

24-07-2001

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5097253 A	17-03-1992	CA 2007098 A WO 9007759 A US 5180003 A	06-07-1990 12-07-1990 19-01-1993
US 4523186 A	11-06-1985	NONE	
US 5443190 A	22-08-1995	NONE	

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

THIS PAGE BLANK (USPTO)